



SAFETY TRAINING LEAFLET 05 INERT GASES (NITROGEN & ARGON)

Doc 23.05/18

EUROPEAN INDUSTRIAL GASES ASSOCIATION AISBL



AVENUE DES ARTS 3-5 • B-1210 BRUSSELS
Tel: +32 2 217 70 98 • Fax: +32 2 219 85 14
E-mail: info@eiga.eu • Internet: www.eiga.eu



SAFETY TRAINING LEAFLET 05 INERT GASES (NITROGEN & ARGON)

Prepared by Safety Advisory Council

Disclaimer

All technical publications of EIGA or under EIGA's name, including Codes of practice, Safety procedures and any other technical information contained in such publications were obtained from sources believed to be reliable and are based on technical information and experience currently available from members of EIGA and others at the date of their issuance.

While EIGA recommends reference to or use of its publications by its members, such reference to or use of EIGA's publications by its members or third parties are purely voluntary and not binding.

Therefore, EIGA or its members make no guarantee of the results and assume no liability or responsibility in connection with the reference to or use of information or suggestions contained in EIGA's publications.

EIGA has no control whatsoever as regards, performance or non performance, misinterpretation, proper or improper use of any information or suggestions contained in EIGA's publications by any person or entity (including EIGA members) and EIGA expressly disclaims any liability in connection thereto.

EIGA's publications are subject to periodic review and users are cautioned to obtain the latest edition.



Table of Contents

| | | |
|-----|---|---|
| 1 | Introduction | 1 |
| 1.1 | Safety leaflets | 1 |
| 1.2 | Comprehension tests..... | 1 |
| 2 | Inert gases | 1 |
| 2.1 | Hazards of inert gases..... | 1 |
| 2.2 | Inert gases cylinder filling specific hazards and prevention measures. | 1 |
| 2.3 | Liquid inert gases storage hazards and prevention measures..... | 2 |
| | Appendix 1 – Inert Gases (Nitrogen & Argon) – Test Questions | 3 |
| | Appendix 2 – Inert Gases (Nitrogen & Argon) – Test Answers | 4 |

Note: this Safety Training Leaflet is taken from Leaflet 4: INERT GASES (NITROGEN AND ARGON) in Doc 23/08 Safety Training of Employees. The leaflet has been put into a new format and revised,

1 Introduction

1.1 Safety leaflets

Safety training leaflets summarise the basic operational safety knowledge which needs to be known by employees working in the gas industry.

Refer to EIGA Doc 23 *Safety Training of Employees* for the various combinations of leaflets which define the scope of safety training for a variety of specific jobs.

Each leaflet addresses a specific topic as identified in the title.

1.2 Comprehension tests

There is a comprehension test for each leaflet, included in **Appendix 1**.

Each test comprises several questions. To pass the test it is suggested that the employee should score 75% at the first attempt. Incorrect answers should be discussed to confirm understanding.

Appendix 2 includes the list of correct answers.

2 Inert gases

Nitrogen is often referred to by its chemical symbol N₂, Argon by its chemical symbol Ar. They are non-flammable, colourless, odourless and tasteless gases. Nitrogen is slightly lighter than air, while Argon is heavier than air. They are essential parts of atmospheric air which normally contains 79 % inert gases (78 % nitrogen + 1 % argon); the balance, 21 %, is oxygen.

2.1 Hazards of inert gases

- The inert gases are not toxic but do not support life and act as asphyxiants. When liquid nitrogen and argon evaporate, the gas produced is very cold and so is much heavier than air. Therefore, it can collect in areas below ground level and confined spaces, such as pits and trenches where the gas may be slow to disperse. A person can become unconscious immediately when entering an atmosphere which contains excessive proportions of inert gases (and, therefore, a shortage of oxygen). If the oxygen concentration is low, death can follow rapidly.
- Before entering vessels and enclosed spaces in which an accumulation of inert gases may have occurred, ensure that the atmosphere has been tested and that the oxygen content is within safe limits (19-23 %). A work permit is required - see Safety Training Leaflet 23 *Work Permit*. Always wear a personal oxygen-monitor
- Ensure that rooms or spaces where inert gases are stored or handled have either good ventilation or that their atmosphere is monitored for oxygen content.
- Do not stop ventilators in rooms where inert gases are stored or handled. Make sure that atmosphere monitoring systems are in operation.

2.2 Inert gases cylinder filling specific hazards and prevention measures.

- Contamination of cylinders with moisture or exposure to other type of stress such as fire or impact is hazardous as it causes corrosion or damage which in turn may cause a pressurised cylinder to burst. A cylinder inspection prior to filling is mandatory.
- You must know how to stop the cylinder filling process in case of an emergency.
- When not connected to the filling rack, cylinders must be capped and secured.

2.3 Liquid inert gases storage hazards and prevention measures

- Liquid inert gases are stored in registered pressure vessels. There is an identification plate on the vessel; you must know what the engraved information means. Tank pressure monitoring and control is critical, overpressure protections must be kept in good condition, operating instructions must be known, uncontrolled deviations must be reported.
- It is hazardous to overfill liquid storage tanks, level in the tank must be monitored.
- A liquid inert gas release in the atmosphere generates a thick cloud made of condensed moisture. Do not expose yourself to the cloud and try to get out of the cloud to breathe.

Appendix 1 – Inert Gases (Nitrogen & Argon) – Test Questions

Tick the correct answer (s) or write in the blank spaces as requested.

1. The inert gases are not toxic but do not support life and act as....?

2. Atmospheres in which nitrogen or argon accumulates are recognised by their characteristic smell:
A. True **B. False**
3. If a cryogenic tank is filled with an inert cryogenic liquid it must be done _____
_____ to avoid overfilling.
4. Tick at least three items of personal protection equipment that must be used when handling cryogenic liquids.
A. Cryogenic gloves **D. Protective footwear**
B. Face shield **E. Antistatic footwear**
C. Safety harness **F. Long-sleeved shirt**
5. Which risks could be caused by spilled cryogenic inert gases?
A. Oxygen enrichment **C. Risk of explosion**
B. Embrittlement of materials **D. Asphyxiation**
6. Tick at least three characteristics of nitrogen:
A. Tasteless **E. Flammable**
B. Colourless **F. Toxic**
C. Combustible **G. Odourless**
D. Inert **H. Similar density to air**
7. The minimum percentage of oxygen in air for a safe environment is 19.5%
A. True **B. False**
8. State three common properties of argon and nitrogen:

Appendix 2 – Inert Gases (Nitrogen & Argon) – Test Answers

1. Asphyxiants
2. B
3. "Slowly and the level monitored"
4. A, B, D and F
5. B and D
6. A, (tasteless), B (colourless), D (inert), G (odourless) and H (similar density to air)
7. A
8. * Inert. * Colourless.
* Tasteless. * Compressed gases.
* Odourless * Cryogenic liquid